

# BP400 AG

LUBRIFICADOR  
ENGRASADOR  
GRAISSEUR  
SCHMIERNIPPEL  
LUBRICATION POINT

CREMALHEIRA E CARRETO EM FERRO FUNDIDO  
CORONA Y PIÑÓN EN HIERRO FUNDIDO  
COURONNE ET PIGNON EN FONTE  
ZAHNKRANZ UND ZAHNRAD AUS GUSSEISEN  
CAST IRON GEAR RING

BOCA REFORÇADA  
BALDE COM 3 AMASSADORES DUPLOS SOLDADOS  
BOCA REFORZADA, BOMBO  
CON 3 PALAS MEZCLADORAS DOBLES SOLDADOS  
OUVERTURE RENFORCÉE  
3 PALES DOUBLES DE MALAXAGE MÉCANO-SOUDÉE  
GESTÄRKT MÜNDUNG MIT  
3 GESCHWEISSTEN MISCHSCHAUFELN  
DRUM WITH REINFORCED OPENING  
3 DOUBLE MIXING BLADES

PEDAL REFORÇADO  
PEDAL REFORZADO  
PÉDALE RENFORCÉE  
ROBUSTER PEDAL  
REINFORCED PEDAL

ESTRUTURA EM TRIÂNGULO, FERRO EM "U"  
CHASIS EN TRIÂNGULO, HIERRO "U"  
CHASSIS EN TRIANGLE, COLONNE EN FER "U"  
TRIANGULIERT RAHMEN IN "U" FORM  
TRIANGLE STRUCTURE, U STEEL

CARDIN MAQUINADO  
CARDAN MECANIZADO  
CARDIN USINÉ  
CARDIN ÜBERTRAGUNG  
MACANIZED CARDIN

PROTEÇÃO DE CREMALHEIRA OPCIONAL  
PROTECCIÓN DE RACK OPCIONAL  
PROTECTION DE LA COURONNE EN OPTION  
ZAHNRADSCHUTZALS OPTION  
OPTIONAL GEAR RING PROTECTION

## BETONEIRA PROFISSIONAL AGRÍCOLA HORMIGONERA PROFESIONAL AGRICOLA BÉTONNIÈRE PROFESSIONNELLE AGRICOLE LANDWIRTSCHAFT PROFI BETONMISCHER PROFESSIONAL CEMENT MIXER



400	35 Kg + 35 Kg	210 Kg	2,60 m <sup>3</sup> /h	360 L	290 L	1700 x 895(1290) x 1260
DOSAGEM	PESO SEM MOTOR	PRODUÇÃO HORÁRIA	CAPACIDADE TOTAL DO BALDE	CAPACIDADE MÁXIMA DE MISTURA	DIMENSÕES	
CAPACIDAD	PESO SIN MOTOR	PRODUCCIÓN HORARIA	CAPACIDAD MÁXIMA DEL BOMBO	CAPACIDAD MÁXIMA DE MEZCLA	DIMENSIONES	
DOSAGE	POIDS SANS MOTEUR	PRODUCTION HORAIRE	CAPACITÉ DE LA CUVE	CAPACITÉ MAX DE MALAXAGE	DIMENSIONS	
DOSIERUNG	GEWICHT OHNE MOTOR	STUDENPLAN PRODUKTION	TROMMELINHALT	MISCHLEISTUNG	DIMENSIONEN	
DOSAGE	WEIGHT WITHOUT ENGINE	PRODUCTION PER HOUR	DRUM CAPACITY	MAXIMUM MIXING CAPACITY	DIMENSIONS	