

BP RLAT EVO

BETONEIRA PROFISSIONAL REBOCÁVEL HORMIGONERA PROFESIONAL REMOLCABLE BÉTONNIÈRE PROFESSIONNELLE TRACTABLE PROFI ANHÄNGBARER BETONMISCHER PROFESSIONAL TOWABLE CEMENT MIXER

PÉS GALVANIZADOS

PIES GALVANIZADOS

PIEDS GALVA

GALVANISIERTEFUßE

GALVANIZED FEET

CREMALHEIRA E CARRETO EM FERRO FUNDIDO NODULAR

CORONA Y PIÑON EN HIERRO FUNDIDO NODULAR

COURONNE ET PIGNON EN FONTE NODULAIRE

ZAHNKRANZ UND ZAHNRAD AUS GUSSEISEN

NODULAR CAST IRON GEAR RING

ESTRUTURA, BALDE E BOCA REFORÇADOS

BALDE COM 3 AMASSADORES DUPLOS SOLDADOS

ESTRUTURA, CUBO Y BOCA REFORZADOS

BOMBO CON 3 PALAS MEZCLADORAS DOBLES SOLDADOS

STRUCTURE, CUVE ET OUVERTURE RENFORCÉE

3 PALES DOBLES DE MALAXAGE MÉCANO-SOUDÉE

RAHMEN, TROMMEL UND MUND

3 GESCHWEISSTEN MISCHSCHAUFELN

REINFORCED STRUCTURE, DRUM AND OPENING

3 DOUBLE MIXING BLADES

TIMON COM GANCHO DE ENGATE HOMOLOGADO

TIMON CON GANCHO DEL REMOLQUE HOMOLOGADO

TIMON HOMOLOGUÉ DOUBLE POSITION

HOMOLOGIERT ANKUPPELUNG

APPROVED DOUBLE TUBE POSITION

2 ROLAMENTOS CÔNICOS

3 ROLAMENTOS TRANSMISSÃO

2 RODAMIENTOS CÔNICOS

3 RODAMIENTOS TRANSMISION

2 ROULEMENTS CONIQUES SUR L'AXE DE CUVE

ET 3 ROULEMENTS SUR L'AXE DU PIGNON

2 KONISCHELAGER

3 GETRIEBELAGER

2 CONICAL BEARINGS

3 TRANSMISSION BEARINGS


PROTEÇÃO DE CREMALHEIRA OPCIONAL

PROTECCIÓN DE RACK OPCIONAL

PROTECTION DE LA COURONNE EN OPTION

ZAHNRADSCHUTZALS OPTION

OPTIONAL GEAR RING PROTECTION



500	2 x 50 Kg + 25 Kg	285 Kg	3,30 m ³ /h	450 L	390 L	1950 x 1230 x 1650
400	35 Kg + 35 Kg	251 Kg	2,60 m ³ /h	360 L	290 L	1800 x 1100 x 1600
280	25 Kg + 25 Kg	189 Kg	2,00 m ³ /h	260 L	200 L	1700 x 960 x 1520

DOSAGEM
CAPACIDADE
DOSAGE
DOSIERUNG
DOSAGE

PESO SEM MOTOR
PESO SIN MOTOR
POIDS SANS MOTEUR
GEWICHT OHNE MOTOR
WEIGHT WITHOUT ENGINE

PRODUÇÃO HORÁRIA
PRODUCCIÓN HORARIA
PRODUCTION HORAIRE
STUDENPLAN PRODUKTION
PRODUCTION PER HOUR

CAPACIDADE TOTAL DO BALDE
CAPACIDAD MÁXIMA DEL BOMBO
CAPACITÉ DE LA CUVE
TROMMELINHALT
DRUM CAPACITY

CAPACIDADE MÁXIMA DE MISTURA
CAPACIDAD MÁXIMA DE MEZCLA
CAPACITÉ MAX DE MALAXAGE
MISCHLEISTUNG
MAXIMUM MIXING CAPACITY

DIMENSÕES
DIMENSIONES
DIMENSIONS
DIMENSIONEN
DIMENSIONS



CONTA HORAS
CONTA HORAS
COMPTEUR D'HEURES
STUNDENZÄHLER
HOUR METER

OPÇÃO OPCION OPCIONALE OPTION OPTION

ARRANQUE ELÉCTRICO
ARRANQUE ELÉCTRICO
DÉMARRAGE ÉLECTRIQUE
ELEKTRO INBETRIEBNAHME
ELECTRIC STARTER



 MOTORIZAÇÃO MOTORIZACION MOTORISATION MOTOR MOTORIZATION	 2,0 cv 500 - 3,0 cv	 6X 160 5,5 hp	 XR 550 3,5 hp	 CR 750 5,5 hp	 CR 950 6,5 hp	 EX 17 5,7 hp	 KM170 3,8 hp	 KD15-225 4,5 hp	 KD15-350 7,0 hp
	ELÉTRICO	GASOLINA	GASOLINA	GASOLINA	GASOLINA	GASOLINA	DIESEL	DIESEL	DIESEL
	ELECTRICO	GASOLINA	GASOLINA	GASOLINA	GASOLINA	GASOLINA	DIESEL	DIESEL	DIESEL
	ÉLECTRIQUE	ESSENCE	ESSENCE	ESSENCE	ESSENCE	ESSENCE	DIESEL	DIESEL	DIESEL
	ELEKTRO	BENZIN	BENZIN	BENZIN	BENZIN	BENZIN	DIESEL	DIESEL	DIESEL
ELECTRICAL	PETROL	PETROL	PETROL	PETROL	PETROL	DIESEL	DIESEL	DIESEL	